

CHINON

CM-4

**SEMI-AUTOMATIC SLR WITH FULL MANUAL CONTROL
AND BAYONET MOUNT LENS**

FEATURES

- Creative full manual control VIA match LED exposure system.
- Seiko designed shutter with speeds from 1 second to 1/1000.
- Instant responding silicon blue cell employed in the center weighted full aperture metering system.
- Compact/lightweight design.
- Accepts lenses with universal bayonet mount and accepts thread mount lenses with optional adapter.
- Memo holder so that you always know what type of film is in your camera.

ACCESSORIES

PRODUCT NUMBER DESCRIPTION

27540	Black custom case
28900	S-180 Automatic electronic flash
28910	S-240 Dedicated automatic electronic flash
28920	S-280 Dedicated automatic electronic flash
28350	Right angle finder
28202	Eyepiece diopter -3.0
28212	Eyepiece diopter +1.0

28222	Eyepiece diopter +3.0
28815	Lens cap (49mm)
28880	Neck strap for CE-4, CA-4, CM-4, CS-4
28405	Extension tube set (12, 20, 36mm)
28415	Extension bellows
28560	Rubber eyepiece
6020	Lens hood (49mm)
28640	Metal table tripod



35mm SLR CAMERA

CHINON

CM-4

SPECIFICATIONS

- **Type:** 35mm SLR compact camera with LED type light measuring system.
- **Picture Format:** 24 x 36mm
- **Lens Mount:** Chinon Universal Bayonet Mount.
- **Mirror:** Large, Quick return, shockless system.
- **Shutter:** Seiko MFC metal focal plane shutter.
- **Shutter Speeds:** 1 sec. — 1/1000 sec., "B".
- **Viewfinder:** Fixed eye-level pentaprism, central split image with microprism collar and ground glass.
- **Viewfinder Magnification:** 0.87 x (@50mm, ∞).
- **Viewfinder Visibility:** 92%.
- **Exposure Meter:** TTL, Center weighted full aperture system employing one silicon blue photo cell, 3 step exposure indicator with 3 LED's.
- **Exposure Range:** EV + 2 (F/1.9, 1 sec.) to EV + 18 (F/16, 1/1000 sec.) — ASA100 F/1.9 lens.
- **Meter ON/OFF Switch:** Meter switch is activated when shutter release button is pressed, meter remains on for several seconds after finger is lifted off release button.


- **ASA Range:** 25 - 1600 (DIN 15 - 33) with safety lock.
- **Film Advance:** Single stroke in an arc of 130° with 25° stand off.
- **Film Counter:** Automatically indicates number of exposures and resets to "S" when camera back is opened.
- **Film Rewind:** Folding crank type.
- **Accessory Shoe:** Hot shoe type with X sync.
- **Action Lamp:** Red LED illuminates while the shutter operates.
- **Synchronization:** Strobe Sync. at 1/60 sec.
- **Power Source:** Two 1.5V silver oxide G-13 batteries (S-76 type).
- **Battery Test:** Built-in with LED indicator.
- **Accessories:** Multi-coated lenses, Auto electronic flashes carrying case, and many more.
- **Body Dimensions:** 135.5 (W) x 86.0 (H) x 50.5 (D) mm. (5.33" x 3.78" x 1.99").
- **Body Weight:** 455 grams (16.05 oz.).

STANDARD PACKAGING WITH F/1.7 MC LENS #23003

PRODUCT NUMBER	DESCRIPTION
24871	CM-4 Body
26200	50mm f/1.7 MC lens
28815	Snap-in front lens cap (49mm)
28880	Shoulder strap with pad and "D" rings
----	Rear lens cap
----	Body cap
----	Two G-13/S-76 batteries
----	Instruction book

AVAILABLE AS FOLLOWS:

PRODUCT NUMBER	DESCRIPTION
23011	CM-4 with 50mm f/1.9 lens
23003	CM-4 with f/1.7 MC lens
23007	CM-4 with f/1.4 MC lens
23001	CM-4 with 45mm f/2.8 lens
24871	CM-4 Body only



VIEWFINDER

1. Over exposure Red LED
2. Correct exposure Green LED
3. Under exposure Red LED
4. Split image rangefinder
5. Microprism collar
6. Ground glass

